

# Teltonika DualCam

#### ADVANCED TRACKER WITH DUAL CAMERA

Teltonika DualCam solution is perfect for capturing videos or pictures of the events that might occur on the road, e.g. crash. Mounted on the vehicle front window, two cameras are used, front and rear, to record videos before and after the events, take photos periodically or by request and send all data to the server. Besides, the innovative solution ensures the safety of passengers as recordings are made of what is happening inside the vehicle.

You can also get the videos or pictures on all scenarios, such as green driving, idling detection, unplug detection, towing detection, or geofence, by sending a request from server. Connected over RS232, trackers FMC125 with dual camera support High Efficiency Video Coding (H265) for a fast video file delivery. For an easy implementation with server, we prepared a universal communication protocol.

### VIDEO SENDING TRIGGER

By Crash scenario, DIN1/DIN2 (panic button, seat belts and etc.)

## VIDEO/PHOTO BY REQUEST

Available from both cameras with SMS/GPRS command

#### PERIODIC PHOTO SENDING

Automatically every configured period



| Technical data                        |  |
|---------------------------------------|--|
| Supported by                          | FMC125, FMM125, FMU125, FMU126, FMB125   |
| Day & Night Vision Effect             | Day (Color), Night (Black & White)   |
| Angle of View                         | Horizontal 120°, Vertical 70°  |
| Dual Camera                           | Front and Rear (equal characteristics)   |
| Camera casing dimensions              | 126.2 x 36.6 x 36.6 mm   |
| Camera mounting                       | Sticky tape (3M) or screws   |
| Certificates                          | CE, FCC, RoHS  |
| Electrical parameters                 |  |
| Input voltage range                   | 9-36 V   |
| Working temperature and humidity      | 30C~85C Humidity<90%   |
| Stand-by electric current             | 60 mA  |
| Function parameter                    |  |
| Real time clock (RTC) synchronization | Available over FM (via NTP, NITZ or GNSS)  |
| Picture resolution                    | 1280 x 720 (default) (50KB transfer period 18 sec), Configurable: 160 x 120; 320 x 240; 640 x 480; 1920 x 1080 |
| IR Distance                           | 2 Meters   |
| Cable length                          | RS232 (3.5 m)  |
| Video compression                     | H.265  |
| Video resolution                      | 720P (20 sec. – 6MB, transfer period ~320sec.)   |
| Video storage                         | 2psc. MicroSD card (Max 64G up to 72 hours of video)   |